

Six3 Tile®

PRODUCT SPECIFICATIONS

Six3 Tile is an innovative, patented tile product that is a single, integrated system providing the classic look and feel of traditional ceramic tile without the need for costly specialized skills or tools.

Ideal for bathroom tub surrounds, showers, kitchen backsplashes and walls, these lightweight, flexible yet durable large format sheets install with a speed that is unmatched, resulting in a cost-efficient, professional look in about an hour.

Six3 Tile is also fully customizable to produce virtually any tile pattern and color - including complex designs and custom logos.



Standard Tub Surround Kit - 9 sheets

Standard Install Kit consist of:

Six (6) side pieces

- 36" wide by 24" tall by ¼" thick


Three (3) back pieces

- 60" wide by 24" tall by $\frac{1}{4}$ " thick (2 pcs)
- 60" wide by 24" tall by $\frac{1}{4}$ " thick (1 pc)


Total square feet: 64

Covers a 70" x 60" x 36" tub surround

Standard Color: Gloss White



*Pictured: 4"x16" Subway - refer to SKUs for specific patterns



Standard Shower Kit - 12 sheets

Standard Install Kit consist of:

Eight (8) side pieces


- 36" wide by 24" tall by ¼" thick Four (4) back pieces

- 60" wide by 24" tall by ¼" thick

Total square feet: 84

Covers a standard 36" x 60" x 8' ceiling

Standard Color: Gloss White



*Pictured: 4"x16" Subway - refer to SKUs for specific patterns



Standard Back Splash Kit- 5 sheets


Example: 3"x6" Subway Pattern:

Overall dimensions (each sheet):

- 19" wide by 47" long by ¼" thick
- Square feet per board: 6
- Total kit square feet: 30


Standard Colors:

- White, Passive Gray and Software Gray
- Custom colors available; minimum quantity required



*Pictured: 3"x6" Subway - refer to SKUs for specific patterns

COLORS



WARRANTY

One-Year Limited Warranty

See Six3 Tile® warranty information for more details.

PERFORMANCE TESTS

Salt Spray Test, ASTM B117: 300 hours per the SW PDS for Polane 8910

Humidity, ASTM D2247,100°F, 100% RH: 1000 hours per the SW PDS for Polane 8910

Pencil Hardness, ASTM D3363: 2H

Chip resistance: Excellent, 7A
Water Immersion: 96 hours: No effect
Water spot test: 24 hours: No effect

Chemical Resistance Test (24 hr covered spot test):

Engine Oil:

Diesel Fuel:

Unleaded Gasoline:

No visual effect

Flame Spread: 50

Smoke Developed: 950

National Fire Protection Association (NFPA) Fire Rating:

International Code Council (ICC) Fire Rating:

Class 2

Mold and mildew test, ASTM D3273:

Water Absorption Coefficient and Resistance, ASTM D570:

Passed

Water Vapor Permeance, ASTM E96: <0.5 perms

APPLICATION

VERTICAL, INDOOR APPLICATION ONLY! Approved for use as a stove backer near or behind a cooking range where the heat source is not closer than 6 inches. Not approved for flooring, load bearing or outdoor applications.

Interior Ceramic Tile Substitute complying with the following:

Type: Mold and mildew resistant polyvinyl chloride (PVC).

Thickness: nominal ¼ inch (6 mm).

Finished Coating: Polyurethane Enamel.

Board Size: various depending on application.

Meets IBC Section 307.2, Bathtub and shower spaces.

Meets HUD Code Section 3280.202 with subsection 3280.203 Flame spread limitations

and fire protection requirements.

DELIVERY, STORAGE and HANDLING

Deliver and store products in manufacturer's unopened packaging bearing the brand name and manufacturer's identification until ready for installation.

Store materials on level supports off the ground to prevent sagging. Cover loosely with waterproof material to prevent condensation from forming while protecting against weather, direct sunlight, surface contamination, and construction traffic.

Handle materials to avoid damage to edges and surfaces.

INSTALLATION ACCESSORIES

Six3 Tile® can be installed using standard construction adhesives.

When using grout, as recommended, use only UNSANDED or NON-Sanded grout. Any other grout will likely dull the surface of the **Six3 Tile** product.

Do not use any reciprocating power tools such as jigsaws or sawzalls to cut the product to prevent rough edges along the cut line. If using power tools, use only oscillating or circular saws.

Reference the Six3 Tile installation instructions and recommended tools list for further details.

Kitchen Backsplash	n 5 tile sheets per pack			
Style	Color	Sheet Size	SF/Pack	SKU
Subway (3"x6")	White (SW7757)	19"x47"	30.0	AP03-01-SS-01-5
Subway (3"x6")	Passive Gray (SW7064)	19"x47"	30.0	AP03-02-SS-01-5
Subway (3"x6")	Software Gray (SW7074)	19"x47"	30.0	AP03-08-SS-01-5
Subway (3"x6")	Grizzle Gray (SW7068)	19"x47"	30.0	AP03-09-SS-01-5
Herringbone (3"x6")	Snowbound (SW7004)	19"x47"	30.0	AP03-14-HB-01-5
Hexagonal (2"x2")	Snowbound (SW7004)	19"x47"	30.0	AP03-14-HX-04-5
Subway (3"x6")	Black Emerald (SW2936)	19"x47"	30.0	AP03-03-SS-01-5
Subway (3"x6")	Matte Passive Gray (SW7064)	19"x47"	30.0	AP03-02M-SS-01-5

Tub Surround 9	9 tile sheets per pack	3 rows		
Style	Color	Size (side x back walls)	SF/Pack	SKU
Subway (4"x16")	White (SW7757)	2 ea 30"x70" & 1 ea 60"x70"	64.0	ATSP-30-70-01-SS-08-9
Subway (3"x6")	White (SW7757)	2 ea 36"x70" & 1 ea 60"x70"	64.0	ATSP-36-70-01-SS-01-9
Subway (4"x16")	White (SW7757)	2 ea 36"x70" & 1 ea 60"x70"	64.0	ATSP-36-70-01-SS-08-9

Shower 12 tile sheets per pack 4 rows 8-foot ceiling				
Style	Color	Size (side x back walls)	SF/Pack	SKU
Subway (4"x16")	White (SW7757)	2 ea 36"x94" & 1 ea 60"x94"	84.0	ATSP-36-94-01-SS-08-12

SW7757 White	SW7064 Passive Gray	SW7074 Software Gray
Standard Color	Standard Color	Standard Color

To view the complete line of Sherwin-Williams colors available, visit <u>www.sherwin-williams.com/visualizer</u>.



www.SIX3TILE.com

119 Grace Avenue | Lancaster, South Carolina 29720

