

DuraSafe™ Vent Installer's Kit


EVERYTHING YOU NEED FOR EASY INSTALLATION

PTN: 4396013RB


- Pre-attached elbow/wall-offset saves time
- Standard clearance 4½"
- (1) 4' pipe section attached to a close elbow
- (1) 4' pipe section attached to a wall-offset elbow
- (1) Extension collar
- (2) Clamps for wall and dryer connection




- 1 Clamp one elbow/vent section to dryer and connect one wall-offset elbow/vent to wall.



- 2 Extend vent toward top of dryer, then push dryer to wall.



- 3 From over the top, snap vent together. Use extra clamps or extension collar to offset if needed.



Dryer Venting SKU List

KEY	PTN	VENTING DESCRIPTION
	4396013RB	Installer's kit
	4396652RB	4' Gas line dryer hook-up kit
	W10182829RB	4', 3-Wire (cord) electric dryer hook up kit
	W10182830RB	4', 4-Wire (cord) electric dryer hook up kit
A	4396033RP	5' Metal, crush-resistant flexible dryer venting
A	4396727RP	8' Metal, crush-resistant flexible dryer venting
A	4396010RP	6' Snap-Lock™ metal, crush-resistant flexible dryer venting
A	4396009RP	5' Snap-Lock™ metal, crush-resistant flexible dryer venting
B	4396007RW	Through-the-wall vent hood
B	8212662	4" Flush-mounting louvered vent hood
C	4396008RP	(2) 4" Steel clamps
D	4396006RW	Close elbow
E	8171587RP	0–5" Metal vent periscope
E	4396037RP	0–18" Metal vent periscope
E	4396011RP	18–29" Metal vent periscope
E	4396014	29–50" Metal vent periscope
E	4392892	In-wall metal vent periscope extends 29–77" between wall studs

See next page for key.

See Account Manager for details.

LAUNDRY

Venting Configuration – Determine the Best Fit for Your Needs

A



PTN: 4396009RP

5' Snap-Lock™ metal, crush-resistant, flexible dryer venting

One end with Snap-Lock™ male fitting and the other with slit-cuff to use as either male or female for standard 4" openings. Includes (2) clamps.

A



PTN: 4396010RP

6' Snap-Lock™ metal, crush-resistant, flexible dryer venting

One end with Snap-Lock™ male fitting and other end with Snap-Lock™ female fitting for standard 4" openings. (Best choice for fast installation with collar(s) and for creating longer runs with other vent pipes.)

A



PTN: 4396033RP / 4396727RP

5' and 8' Metal, crush-resistant, flexible dryer venting

Both ends with slit-cuff to use as either male or female for 4" openings. Includes (2) clamps.

B



PTN: 4396007RW

Through-the-wall vent hood

4" Opening, heavy-duty rigid metal & 10½" pipe with back draft flapper.

B



PTN: 8212662

Flush mounting, louvered vent hood

4" Opening, heavy-duty rigid metal & 10½" pipe with back draft flapper.

C




PTN: 4396008RP

(2) 4" Steel clamps

With phillips/hex head screw. Includes (2) clamps.


Fits Almost Anywhere



REVERSIBLE

Periscope openings can be on the same or opposite side.


Once attached, periscopes can rotate to any position.




ROTATES

Tight Clearance – 2½" or More

Corner outlet beside dryer with short periscope



Wall outlet beside dryer with medium periscope



One Tough Kit



DURASAFE™ VENT INSTALLER'S KIT

PTN: 4396013RB


Everything you need for easy installation

- Pre-attached elbow/wall-offset saves time
- Standard clearance 4½"
- (1) 4' pipe section attached to a close elbow
- (1) 4' pipe section attached to a wall-offset elbow
- (1) Extension collar
- (2) Clamps for wall and dryer connection


See Account Manager for details.

Standard Clearance – 4½" or More

Corner outlet beside dryer



Wall outlet beside dryer



LAUNDRY



Description **6' Snap-Lock™ Flexible Dryer Venting**
Male-female, Snap-Lock™ venting for 4" openings. Fast installation. Metal, crush-resistant.

Part No. **4396010RP**


Pack Type Retail polybag



Description **5' Snap-Lock™ Flexible Dryer Venting**
Duct has one male Snap-Lock™ fitting and one soft-cuff end male fitting that acts as a vent coupling. Metal, crush-resistant.

Part No. **4396009RP**

Pack Type Retail polybag



Description **5' Flexible Dryer Venting**
Includes (2) clamps. Slit-cuff. Metal, crush-resistant. For 4" openings.

Part No. **4396033RP**

Pack Type Retail polybag



Description **Installer's Kit**
The professional's choice for quick and easy installation. See previous page for details.

Part No. **4396013RB**

Pack Type Retail box



Description **18-29" Vent Periscope**
(Closest to wall application, 2½") One male Snap-Lock™ fitting and one extra-long draw-band collar. Beveled ends eliminate floor or side wall interference. Metal.

Part No. **4396011RP**

Pack Type Retail box



Description **0-5" Vent Periscope**
For tight 2½" clearance. One male fitting and one extra-long draw-band collar. Metal.

Part No. **8171587RP**

Pack Type Retail polybag



Description **29-50" Vent Periscope**
(Closest to wall application, 2½") One male Snap-Lock™ fitting & one extra-long draw band collar. Beveled ends eliminate floor or side wall interference. Metal.

Part No. **4396014**

Pack Type FSP polybag



Description **0-18" Dryer Periscope**
(Closest to wall application, 2½") Can be cut-to-fit. One male Snap-Lock™ fitting and one extra-long draw-band collar. Metal.

Part No. **4396037RP**

Pack Type Retail polybag



Description **Close Elbow**
Turns 90° within 4½". Includes Snap-Lock™ fittings and rotating collars.

Part No. **4396006RW**

Pack Type Retail wrap



Description **4" Vent Clamps (2-Pack)**
4" Stainless steel clamp includes Phillips/hex head screw designed to resist stretching.

Part No. **4396008RP**

Pack Type Retail polybag

See Account Manager for details.